

# 65" 4K Wireless Presentation Display



**CDE6520**



- Wireless presentation across devices and rooms
- Easy cast function pairing with USB-C/HDMI dongle
- USB flash drive plug-and-play for photos, music & video
- Multitasking with powerful embedded player & OPS PC slot
- 4K slim bezel commercial display

The ViewSonic® CDE6520 is an 65" 4K wireless presentation display. The built-in screen sharing software\*, ViewBoard® Cast and Display, as well as ViewBoard® Cast USB-C/HDMI dongles enable multiple users, whether on-site or on-line, to participate in conferences and share content with each other simultaneously, transforming the CDE6520 into a dynamic content hub. This reliable commercial display is equipped with a quad-core processor and internal memory, allowing constant multimedia play from internal storage or a USB flash drive. Supporting remote configuration and content management systems, the ViewSonic® CDE6520 is also suitable for diverse signage applications.

\*Chrome, Android, Windows, Mac OS, and iOS compliant

# Start an Easy Group Presentation

## Instant Auto-Casting Across users with a USB-C/HDMI dongle

No setup needed, just plug in and click the dongle to present your content.



## All Content on One Screen Across devices with the app

From side-by-side to multiple screens overview, the display enables all mobile users to share their full HD content.



## Bring All Remote Participants Together

### 1080p 120° web camera

Built-in noise reduction, WDR, and backlight compensation make your meeting's audio-visual quality great in both bright and dark environments.

\*Optional VB-CAM-001



## **Conduct an Engaging Workshop**

### **Single Content to All Displays On-site or across rooms with the app**

Mirror your content to multiple displays for multi-group environments.





**Play Multimedia and Internet Resources**

**Friendly OS Environment Interface**  
**Embedded player with WiFi & OPS PC slots**

\*Optional WiFi module LB-WIFI-001 & OPS PC VPC12-WPO




## Integrated Multimedia Player

USB flash drive plug-and-play for photos, music, and video



## Link with Internet Resources

Web browser



## Quality Image Display for a Modern Meeting

**4K**  
**High brightness with a slim bezel**






**Easy IT Remote Management**


**Intranet/Internet-Based Settings & Content Management**



## vController, SureMDM, Revel Digital and more



## Dimensions & I/O Ports



1. AC In
2. Power Switch
3. Internal Speakers
4. OPS Slot
5. WiFi Slot
6. Menu Controls
7. VESA® Wall Mount 400x200mm
8. HDMI Out
9. SPDIF
10. HDMI In x 2
11. DisplayPort
12. RS232
13. VGA

- 14. Audio In
- 15. USB 3.0 Type A (USB Playback)
- 16. USB 2.0 Type A x 2 (USB Playback)
- 17. Audio Out
- 18. LAN

## Technical Specifications

Display	Panel Size	65"
	Type/ Tech	TFT LCD Module. IPS type, DLED backlight
	Display Area (mm)	1428.48(H) × 803.52(V) (65" diagonal)
	Native Resolution	3840 x 2160
	Aspect Ratio	16:9
	Colors	1.07G colors
	Brightness	450 nits (typ.)
	Contrast Ratio	1200:1 Typ.
	Response Time	8 ms
	Viewing Angles	H = 178, V = 178 typ.
	Backlight Life	30,000 Hours (min)
	Surface Treatment	Anti-glare, 3H hardness, Haze 25%
	Bezel	Slim
	Orientation	Landscape
Touch	Type/Tech	N/A
	Touch Resolution	N/A
	Touch Point	N/A
INPUT	HDMI	x2
	RGB / VGA	x1
	DisplayPort	x1
	DVI	N/A
	S-Video	N/A
	RF (TV)	N/A
	Audio	x1 (3.5mm)
	CVBS	N/A
	YPbPr	N/A
	MIC(Microphone)	N/A
	RS-232	x1
	IR Pass Thru	N/A
	SD/SDHC	N/A
	OPS	x1 (OPS slot)
	WiFi	x1 (Optional WiFi module)
OUTPUT	RGB / VGA	N/A

	HDMI	x1
	DisplayPort	N/A
	DVI	N/A
	Audio	x1 (3.5mm)
	CVBS	N/A
	YPbPr	N/A
	SPDIF	x1 (Fiber)
	RS232	N/A
	IR Pass Thru	N/A
	Remote Control Out	N/A
<b>LAN</b>	RJ45	x1
<b>USB</b>	Type A	2.0 Type A : x 2 (USB Playback), 3.0 Type A : x 1 (USB Playback)
	Type B	N/A
	Mini USB	N/A
	Micro USB	N/A
<b>Micro SD card slot</b>	Micro SD card slot	No
<b>SPEAKERS</b>	SPEAKERS	Max. 16Wx2
<b>COMPATIBILITY</b>	RGB PC/HDMI PC	Up to 1920x1080@60Hz. Refer to timing table
	CVBS	N/A
	S-Video	N/A
	YPbPr	N/A
	HDMI	480i, 480p, 720p, 1080i, 1080p, 4K2K@60Hz
	DisplayPort	480i, 480p, 720p, 1080i, 1080p, 4K2K@60Hz
	DVI	N/A
	Android Version	Android 8.0
<b>POWER</b>	Voltage	100V-240V, 50/60Hz (AC)
	Consumption	Normal 220 W, Max 300 W
<b>ERGONOMICS</b>	Tilt	N/A
	Wall Mount (VESA® )	400x200 mm
<b>OPERATING CONDITIONS</b>	Temperature (°C)	0 to 40°C
	Humidity	20% ~ 80% non-condensing
<b>DIMENSIONS (W x H x D)</b>	Physical (inch / mm)	57.11 x 32.60 x 3.09 in/ 1450.6 x 828.1 x 78.5 mm
	Packaging (inch / mm)	63.19 x 37.99 x 8.66 in/ 1605 x 965 x 220 mm
<b>WEIGHT</b>	Net (lb / kg)	22.95 kg / 50.59 lbs (w/o stand)



	Gross (lb / kg)	33.6 kg/74.07 lbs
<b>REGULATIONS</b>	REGULATIONS	cULus, FCC, Energy Star, EPEAT,MX-CoC, Mexico Energy, CE, CB, RoHS, ErP, REACH, WEEE, Custom Union, UkrSEPRO, RCM, MEPS
<b>PACKAGE CONTENTS</b>	PACKAGE CONTENTS	1. CDE6520 commercial display, 2. Remote control with batteries, 3. Quick start guide, 4. Power cables (1.5mm), 5. HDMI cable , 6. Wall mount screw, 7. RS232 adapter

## ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at **[www.viewsoniceurope.com](http://www.viewsoniceurope.com)**

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.